

## **Rough Terrain Forklift**

Used Rough Terrain Forklift Santa Clara - Forklift trucks utilize two forks to transport pallets and load and unload cargo. Forklifts fall into two main categories, industrial forklifts and rough terrain forklifts. Ideal for working on surfaces that are level and smooth, industrial forklifts are mostly utilized for warehouse applications and loading dock situations. By contrast, the second category of forklifts, rough terrain forklifts, are commonly used to run on uneven and rocky surfaces. Rough terrain forklifts are often seen at construction sites and outdoors. They have the weight capacity, size and tires to handle heavy loads. The tire type is one of the key differences between rough terrain and industrial forklift units. Common road tires, cushion tires are the main kind found on industrial forklifts. Rough terrain forklifts, on the other hand, are fitted with pneumatic tires, a type of tractor tire allowing for better traction and flotation properties. Industrial forklifts are commonly powered by internal combustion engines although a fuel cell or battery electrical source may be used. Internal combustion engines are mainly used by rough terrain units. Types of Class 7 Rough Terrain Forklift Trucks The three types of Class 7 Rough Terrain Forklift Trucks include the rotating telehandler forklifts, telehandler forklifts and straight mast forklifts. Regardless of its type, all rough terrain forklift trucks are designed to handle, as their name suggests, natural rough terrain and disturbed rough terrain typical of construction and military sites. Rough terrain forklift units have better performance and maneuvering options. Safety considerations are taken into account for rough terrain locations with raising loads in difficult environments to keep the operator safe from tipping over. As with all forklift operation, the machine must be in a position to remain stable before lifting, transporting or lowering a load. Rough terrain forklift operators must practice correct lifting techniques to remain stable on the ground.

**Straight Mast Forklifts** Straight mast forklifts are designed to transport building materials around a range of rough terrain sites such as demolition and construction sites. These forklift trucks provide increased maneuverability and accessibility because it is fitted with big, heavy-duty pneumatic cushion tires. These allow the forklift truck to easily travel over rough terrain on the worksite. The majority of straight mast forklifts come in both two wheel and four wheel drive capabilities. Most straight mast forklifts are powered by diesel or propane fuel, allowing them to be used indoors for short periods but are more suited to outdoor applications. The lift capacities of straight mast forklifts are similar to most standard forklifts with a range of approximately 5,000 to 36,000 pounds.

**Telehandler or Telescopic Handler Forklifts** Telehandler or telescopic handler forklift trucks are equipped with a telescoping boom, giving them their name. This telescoping boom allows the forklift truck to pick up and place loads at various distances and lift heights in front of the machine. Better reachability delivers greater flexibility to the forklift operator while placing loads. Standard telehandler forklift units are long and low. They are designed with two wheels located at the front of the forklift with a different pair of wheels found close to the end of the unit. The telescopic boom can be found at the back of the forklift, mounted on a pivot that is attached many feet higher than the frame of the unit. The hydraulic fluid tank and fuel tank are mounted on the opposite side of the cab which is usually situated on the left side of the forklift. The forklift engine and transmission are situated along the center of the machine. This popular design showcases a balanced forklift which is ideal for the machine's stability with lifting, moving and lowering items. Compared to standard forklifts, telehandlers deliver higher lift heights. Also called compact telehandlers or high-reach telehandlers, these forklift trucks can lift their full load capacities from 18 feet, for the compact telehandlers, to 56 feet, for the high-reach telehandlers, into the air. Load capacities are between 5K to 12K pounds. All-terrain forklifts often include all-wheel steering which allows for greater maneuverability. This, along with power shift transmission and other steering features, means that the operator can move the lift in as close proximity to the work area as possible. More recently, Telehandler forklift models have included additional features that incorporate the latest in ergonomics. Spacious cabs and tilted steering are some of the items redesigned for the ultimate comfort and

productive features. These ergonomic upgrades have been shown to lessen repetitive stress injuries and lessen operator fatigue. The majority of telehandler forklifts are operated by a single joystick. The joystick is responsible for the hydraulic system and the boom operations. Telehandler forklifts can also be equipped with non-marking tires which allow them to be used in other applications such as the installation of signs and billboards as well as maintenance on buildings and stadiums. Rotating Telehandler or Roto Telescopic Handler Forklifts Roto telescopic handler forklifts or rotating telehandlers have numerous items in common with the standard telehandler model. The rotating telehandler can lift excessive loads to extreme heights safely and efficiently. The turntable or rotating ability add extra panache. Rotating the forklift a complete three-hundred-and-sixty degrees creates a larger working location without the need of repositioning the forklift. Commonly, rotating telehandlers have another joystick to handle the rotation portion separately from the lift function. As with the standard telehandler forklift, rotating telehandlers are available with added features including power assist steering, four-wheel drive and minimized slip differential on the rear axle to boost traction and for additional safety. Any machine with rotation capabilities will have additional safety measures to consider. Rotating telehandler rough terrain models come with standard stabilizers to establish more safety while rotating loads back and forth. Some rotating telehandlers do not have stabilizers. These units are created to move and work in various aspects of the job site and are easier to reposition without stabilizers. The standard telehandler offers fixed cab components and rotator telehandlers are generally smaller in comparison. Therefore, rotator telehandler units can access smaller loads when compared to standard telehandler units. Rotating telehandlers offer load capacities ranging from 4000 to 10,000 lbs. and lift heights between fifteen to eighty feet. Winch attachments can transform rotator telehandlers and standard models into a crane. This means that these forklifts can sometimes allow a project to forego the need for a crane at the jobsite, saving time, expense and workspace. Advancements for Rough Terrain Forklifts Numerous attachments can be found for rough terrain forklifts including articulating booms, rotating fork carriages, booms, winches and similar items. More rough terrain forklift attachments will be unleashed onto the market in future years thanks to their ability to make the forklift more multi-purpose than ever before. The majority of advancements will be delivered as safety features built to enhance the rough terrain models. Automatic load restriction units and certain safety features have started being implemented. By automatically weighing a load, these systems calculate the loads' safe reach distance while taking the boom angle and its' extension into account. An alarm will go off once the safe distance is reached. This alerts the operator that immediate adjustments need to be made to the boom angle, reach distance or load weight.